

"CHROMALAC"- CLMR FINISH

PRODUCT DESCRIPTION: Excellent blend of modified resin based paint with quick setting property, good water repellency & anti-corrosive property.

USES: The product can be used for long term protection of heated pipelines, exhausted pipes, chimneys, incinerators, engines, boilers, flare stacks etc.

COMPOSITIONS:
Mixer of modified resin pigmented with strong and long life anti-corrosive Pigments.

PROPERTIES:

- Quick drying property.
- Excellent adhesion.
- Excellent water repellent.
- High chemical resistance.

TYPE: Single pack

APPLICATION:
BY SPRAY OR Brush

VISCOCITY:
70 ± 10" /Fc4 / 30 °C.

WEIGHT / LTR:
1.07 ±0.03.

RECOMMENDED DFT:
30-40 Microns

COVERING CAPACITY:
8 Sq.Mtr/ Ltr.

DRYING TIME
Surface Dry: within 15 mins.
Hard Dry: 3 – 4 hrs.

FINISH
Semi glossy to eggshell

COLOUR:
Grey, off white, pale cream, Brown etc

THINNER: Use NDC special thinner for Chromalac -CLMR to adjust viscosity for spraying if required.

DISCLAIMER: The information given in this data sheet is best of our knowledge, observed while tested in ideal condition in our laboratory.

WORKS: POST & VILL & PO: BAMUNARI, NH -2, DELHI ROAD .DIST HOOGHLY, 712205, WEST BENGAL. PHONE: 9830317320

OFFICE: JEEVAN NIWAS, 30A, BLOCK -R, NEW ALIPORE, 2ND FLOOR, FLAT A/5 KOLKATA: 700 053,

CONTACT: +91 9830848300 / 98308 49200 / 9674129944.